



Thermocouple with Handle

Type Designation	TTA
Measuring Range	-200 to + 800 ° C
Common Sensor Types	K,J,N,T,E
Common Diameters	Ø 1.5, 3.0, 6.0mm
Common Sheaths	321 SS
Flexible Cable Detail	7 x 0.2 PVC/PVC (105 ° C)
Transition Max. Temperature	100 ° C
Termination detail	50mm tails, 10mm Tinned
Application Notes	<ul style="list-style-type: none">■ Tough design for industrial use■ Used as insertion probe for food
Special Options	<ul style="list-style-type: none">■ Duplex■ Probe can be Mineral Insulated■ Plug on terminations available for quick connection■ Reduced tips■ High temperature handle■ Higher temperature flexible cable■ Spring relief at transition■ Insulated Exposed or Grounded junction■ Metal or plastic flexible conduit cover■ Tagging

No Diagram Available

Visit the Peak Sensors Online design guide at
www.peakensors.com

PEAK SENSORS LTD

Kelvin House | Station Lane Industrial Estate | Chesterfield | S41 9QX | United Kingdom

TEL: **+44 (0)1246 261999** | FAX: **+44 (0)1246 261888**

The technical information provided on any pages of the Peak Sensors brochure is advisory only and should not be relied on for any design, process or production. We will be pleased to undertake specific technical advisory work under our normal terms of service. Peak Sensors Ltd accepts no responsibility for any loss or damage caused through reliance on any information contained therein.